



Specialist Control Panels
HEATING & VENTILATION

NM230 / LM230 DAMPER ACTUATOR

FEATURES

- For dampers up to approx. 1.5m² (NM230), up to approx. 1.0m² (LM230)
- Power open / close
- Available with auxiliary switch (NM/LM230A-S)
- Direction of rotation selector switch
- IP54 housing (bottom cable entry position)

IMPROVED FUNCTIONAL SAFETY

The damper actuator has no limit switches and is overload-proof. Its stops automatically when it reaches the damper or actuator end stop.

WIRING DETAILS

NM230A / LM230A



NM230A-S / LM230A-S



* check that S1 and S3 make when damper is fully open (you maybe required to use S1 and S2 and insulate S3 if your damper is fitted using a different direction of rotation).

EASY FUNCTIONAL CHECK

A functional check of damper operation is simplicity itself: the gearing can be disengaged by simply pressing a pushbutton on top of the case, while the pushbutton remains depressed, the damper can be operated by hand.

SIMPLE INSTALLATION

The damper actuator is fitted with a universal spindle clamp for quick and easy mounting directly on the damper spindle. The actuator is supplied with an anti-rotational strap for fixing it in position.

The information provided in the literature is believed to be accurate (subject to change without notice), however, use of such information shall be entirely at user's own risk.

ENQUIRIES

+44 (0)1258 480802

Sarum Electronics Ltd

5 – 7 Holland Business Park, Holland Way
Blandford Forum, Dorset, DT11 7TA

www.sarumelectronics.co.uk | info@sarumelectronics.co.uk